



SAFETY DATA SHEET

According to 1907/2006/EC, Article 31

FUEL SYSTEM CLEANER (Tank Additive)

TEC-2000 LTD.

P. O. BOX 285, Hitchin,
HERTS., SG4 9WQ, U.K.

info@TEC-2000.co.uk

PH: 01462-433 660

FAX: 01462-674 468

MOB: 07831-105 386

Version Number: 13

Dated: 16.11.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Trade Name: TEC-2000 Fuel System Cleaner (Tank Additive)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the preparation: Fuel System Cleaner (Tank Additive).

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TEC-2000 LTD., P.O. Box 285, Hitchin, Herts., SG4 9WQ, U.K.

1.4 Emergency telephone number

0044 (Ø) 1462-433 660 - 0044 (Ø) 7831 105386 (24hrs)

UK - National Poisons Emergency: +44 870 600 6266 (24h - health professionals only).

Ireland - National Poisons Information Centre: +353 1 8379964.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:



GHS02



GHS07



GHS08



GHS09

Signal word: Danger

Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics

acetone

Propan-2-ol

Hazard statements:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation
H319	Causes serious eye irritation.
H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT:	Not applicable.
vPvB:	Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Hazardous components:**

EC number: 918-668-5	Hydrocarbons, C9, aromatics	25-50%
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone	10-<25%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	Propan-2-ol	10-<25%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene	10-<25%
	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

After inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting Measures**5.1 Extinguishing media****Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters**Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

SECTION 6: Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Requirements to be met by storerooms and receptacles:**

Store in a cool, dry place in tightly closed receptacles.

Information about storage in one common storage facility:

Store away from oxidising agents.

Further information about storage conditions:

Protect from heat and direct sunlight.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure Controls/Personal Protection**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****67-64-1 acetone**

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm

67-63-0 Propan-2-ol

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
----------------------------	--

1330-20-7 xylene

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

Ingredients with biological limit values:**1330-20-7 xylene**

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
-----------------------------	--

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes

Avoid contact with the eyes and skin

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Material of gloves: Butyl rubber, BR
Nitrile rubber, NBR

Eye protection:

Safety glasses with side-shields (EN 166).

Body protection: Protective work clothing.

SECTION 9: Physical And Chemical Properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form: Liquid.

Colour: Red

Odour: Characteristic.

Odour threshold: Not determined.

pH-value: Not determined.

Melting point/Melting range: <0 °C

Boiling point/Boiling range: 56 °C (IBC)

Flash point: 0 °C

Flammability (solid, gaseous): Not determined.

Ignition temperature: 230 °C

Decomposition temperature: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.

Explosion limits:

Lower: 0.8 Vol %

Upper: 13.3 Vol %

Oxidising properties: Not determined.

Vapour pressure: Not determined.

Density: Not determined.

Relative density at 15 °C: 0.815.

Vapour density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with Water: Partly soluble.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: <7 cSt.

Kinematic: Not determined.

9.2 Other information: No further relevant information available.

SECTION 10: Stability and Reactivity

- 10.1 Reactivity:** No further relevant information available.
- 10.2 Chemical stability**
Thermal decomposition / conditions to be avoided:
 No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions:** No dangerous reactions known.
- 10.4 Conditions to avoid:** Keep away from heat.
- 10.5 Incompatible materials:** Avoid strong oxidants, strong alkalis and strong acids.
- 10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological Information**11.1 Information on toxicological effects****Acute toxicity****LD/LC50 values:****67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000mg/kg (Rabbit)

67-63-0 Propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (Rabbit)
Inhalative	LC50/4h	30 mg/kg (rat)

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (Rabbit)

Primary irritant effect:

- Skin corrosion/irritation:** No irritant effect known.
- Serious eye damage/irritation:** Irritating effect.
- Respiratory or skin sensitisation:** No sensitising effects known.

SECTION 12: Ecological information**12.1 Toxicity**

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects: No further relevant information available.

SECTION 13: Disposal Considerations**13.1 Waste treatment methods****Recommendation:**

Do not allow product to reach sewage system.

Uncleaned packaging**Recommendation:**

Disposal must be made according to official regulations.

Packaging that may not be cleansed must be disposed of in the same manner as the product.

SECTION 14: Transport Information**14.1 UN Number**

ADR, IMDG, IATA

UN 1993

14.2 UN proper shipping name

ADR

1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL (ISOPROPYL ALCOHOL)), ENVIRONMENTALLY HAZARDOUS

IMDG

FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL (ISOPROPYL ALCOHOL)), MARINE POLLUTANT

IATA

FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL (ISOPROPYL ALCOHOL))

14.3 Transport hazard class(es)

ADR, IMDG



Class

3 Flammable Liquids.

Label

3

IATA



Class

3 Flammable Liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Marine pollutant:

Product contains environmentally hazardous substances: Hydrocarbons, C9, aromatics

Yes

14.6 Special precautions for user

Danger code (Kemler):

Warning: Flammable liquids.

EMS Number:

33

F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Excepted quantities (EQ):

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Tunnel restriction code:

D/E

IMDG

Limited quantities (LQ):

1L

Excepted quantities (EQ):

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory Information.**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2012/18/EU

Named dangerous substances - ANNEX I

None of the ingredients are listed.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other Information.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2